

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name 18V BATTERY 6.0AH HEAVY DUTY

Synonyms

CBBAT18 - ITEM NUMBER • LITHIUM ION RECHARGEABLE BATTERY • LITHIUM ION RECHARGEABLE BATTERY (BATTERY PACKS AND PRODUCTS WITH LITHIUM ION CELLS)

1.2 Uses and uses advised against

Uses BATTERIES

1.3 Details of the supplier of the product

Supplier nameRAMSETREID (A DIVISION OF ITW AUSTRALIA LTD) (RAMSET NZ)Address23-29 Poland Road, Glenfield, Auckland, 0627, NEW ZEALANDTelephone+64 9444 3510Emailsales@ramsetreid.co.nz

Website www.ramset.co.nz

1.4 Emergency telephone numbers

| Emergency | +64 9444 3510 |
|---------------|---------------|
| Poison Centre | 0800 764 766 |

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NON HAZARDOUS ACCORDING TO NZ ENVIRONMENTAL PROTECTION AUTHORITY CRITERIA

2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

Do not short circuit, recharge, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion. The Lithium batteries described in this Safety Data Sheet are sealed units which are not hazardous when used according to the recommendations of the manufacturer.

Under normal conditions of use, the electrode materials and liquid electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Exposure may occur as a result of external environmental conditions or in cases of abuse (mechanical, thermal, electrical) which lead to the activation of safety pressure relief valve(s) and/or cause a rupture of the battery container. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.

Batteries are exempt from classification under the HSNO Act due to being an enclosed article. The materials contained in this product may only represent a hazard if the integrity of the cell or battery is compromised; physically or electrically abused.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

| Ingredient | CAS Number | EC Number | Content |
|--------------------|------------|-----------|---------------|
| CARBON | 7440-44-0 | 231-153-3 | Not Available |
| GRAPHITE | 7782-42-5 | 231-955-3 | Not Available |
| LITHIUM OXIDE | 12057-24-8 | 235-019-5 | Not Available |
| LITHIUM PHOSPHATE | 10377-52-3 | 233-823-0 | Not Available |
| ORGANIC SOLVENT(S) | - | - | Not Available |



PRODUCT NAME 18V BATTERY 6.0AH HEAVY DUTY

| POLYVINYLDIENE FLUORIDE | - | - | Not Available |
|-----------------------------|---|---|---------------|
| LITHIUM ION MANGANESE OXIDE | - | - | Not Available |
| LITHIUM SALT(S) | - | - | Not Available |

Ingredient Notes

The product does not contain metallic lithium or lithium alloys.

4. FIRST AID MEASURES

4.1 Description of first aid measures

- **Eye** Exposure is considered unlikely unless casing is damaged. Flush gently with running water. Seek medical attention if irritation develops.
- Inhalation Exposure is considered unlikely. Due to product form / nature of use, an inhalation hazard is not anticipated.
- Skin Exposure is considered unlikely unless casing is damaged. Gently flush affected areas with water. Seek medical attention if irritation develops.
- Ingestion For advice, contact the National Poisons Centre on 0800 764 766 (0800 POISON) or +643 479 7248 or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form. Rinse mouth with water.
- **First aid facilities** Eye wash facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

Adverse effects not expected from this product. Exposure to battery contents may cause irritation and potential burns.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent. Do NOT use water. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Contents react with water. May explode if exposed to high temperatures due to pressure build up in battery casing. Lithium may burn in a fire situation and may be ejected from the battery. Damaged cells may evolve toxic and flammable vapours. Exposure to fire or temperature above 130 °C may cause explosion.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

4W

- 4 Dry Agent (water MUST NOT be allowed to come into contact with substance).
- W Risk of violent reaction or explosion. Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible. If battery is broken or damaged, absorb liquid with sand or similar. Contain spillage, then collect and place in suitable containers for disposal. CAUTION: Avoid exposure to contents.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.



7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Take measures to prevent exposure to electrostatic discharge. Keep away from naked flames.

7.2 Conditions for safe storage, including any incompatibilities

Store tightly sealed in a cool, dry, well ventilated area, removed from water, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Store below 50°C.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

| Ingredient | Reference | TWA | | STEL | |
|--|-----------|-----|-------|------|-------|
| ingredient | Reference | ppm | mg/m³ | ppm | mg/m³ |
| Fluorides, as F | WES [NZ] | | 2.5 | | |
| Graphite, all forms except graphite fibres | WES [NZ] | | 3 | | |
| Manganese, dust & compounds (as Mn) | WES [NZ] | | 1 | | |
| Manganese, fume (as Mn) | WES [NZ] | | 1 | | 3 |

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

No special precautions are normally required when handling this product. Maintain vapour levels below the recommended exposure standard.

PPE

| Eye / Face | Not required under normal conditions of use. |
|-------------|--|
| Hands | Wear PVC or rubber gloves. |
| Body | Not required under normal conditions of use. |
| Respiratory | Not required under normal conditions of use. |



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| Appearance | ENCLOSED BATTERY |
|-----------------------|------------------|
| Odour | SLIGHT ODOUR |
| Flammability | NON FLAMMABLE |
| Flash point | NOT RELEVANT |
| Boiling point | NOT AVAILABLE |
| Melting point | NOT AVAILABLE |
| Evaporation rate | NOT AVAILABLE |
| рН | NOT AVAILABLE |
| Vapour density | NOT AVAILABLE |
| Specific gravity | NOT AVAILABLE |
| Solubility (water) | INSOLUBLE |
| Vapour pressure | NOT AVAILABLE |
| Upper explosion limit | NOT AVAILABLE |
| Lower explosion limit | NOT AVAILABLE |
| | |

ChemAlert.

PRODUCT NAME 18V BATTERY 6.0AH HEAVY DUTY

9.1 Information on basic physical and chemical properties

| Partition coefficient | NOT AVAILABLE |
|---------------------------|---------------|
| Autoignition temperature | NOT AVAILABLE |
| Decomposition temperature | NOT AVAILABLE |
| Viscosity | NOT AVAILABLE |
| Explosive properties | NOT AVAILABLE |
| Oxidising properties | NOT AVAILABLE |
| Odour threshold | NOT AVAILABLE |
| | |

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Heat above 70°C or incinerate. Deform. Mutilate. Crush. Pierce. Disassemble. Recharge. Short circuit. Expose over a long period to humid conditions. If an upper temperature limit of (e.g. 130°C) is exceeded, the batteries are in danger of bursting.

10.5 Incompatible materials

Battery contents are incompatible with water (evolving flammable gas), oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve hydrogen and lithium oxides when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

| Acute toxicity | No specific acute toxicity data exists for this product. Batteries consist of a hermetically sealed metallic container containing a number of chemicals and materials of construction that may be hazardous upon release. Over exposure considered unlikely unless battery ruptures and contact with contents occurs. Contents may be harmful. |
|-----------------------------|--|
| Skin | Not classified as a skin irritant unless the battery ruptures. Contact with contents may cause irritation, redness, dermatitis and possible burns with prolonged contact. |
| Еуе | Not classified as an eye irritant unless the battery ruptures. Contact with contents may cause irritation, redness and possible burns with prolonged contact. |
| Sensitisation | Not classified as causing skin or respiratory sensitisation. |
| Mutagenicity | No evidence of mutagenic effects. |
| Carcinogenicity | No evidence of carcinogenic effects. |
| Reproductive | No relevant or reliable studies were identified. |
| STOT - single exposure | Not classified as causing organ damage from single exposure. Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures. Exposure to contents may cause respiratory irritation. |
| STOT - repeated exposure | Not expected to cause organ effects from repeated exposure. Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures. |
| Aspiration | Not relevant. |

12. ECOLOGICAL INFORMATION

12.1 Toxicity

This product may be hazardous to the environment if not properly used or disposed of. Do not let internal components enter the marine environment. Avoid release to waterways, wastewater or ground water.

12.2 Persistence and degradability

This product is not readily biodegradable.



PRODUCT NAME **18V BATTERY 6.0AH HEAVY DUTY**

12.3 Bioaccumulative potential

Limited information was available at the time of this review.

12.4 Mobility in soil

This product has low mobility in soil.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal

Reuse or recycle where possible. Return to manufacturer/supplier. Contact your state EPA or the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005; NZS 5433:2012, UN, IMDG OR IATA



| | LAND TRANSPORT (NZS 5433) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|--------------------------------|---|---|---|
| 14.1 UN Number | 3480 | 3480 | 3480 |
| 14.2 Proper Shipping Name | LITHIUM ION BATTERIES (including lithium ion polymer batteries) | LITHIUM ION BATTERIES (including lithium ion polymer batteries) | LITHIUM ION BATTERIES (including lithium ion polymer batteries) |
| 14.3 Transport hazard class | 9A | 9A | 9A |
| 14.4 Packing Group | II | II | II |

14.5 Environmental hazards

Not a Marine Pollutant

14.6 Special precautions for user

Hazchem code 4W

Other information

Transportations of cells or batteries packed with equipment or contained in equipment have to follow the appropriate regulations for UN3091.

15. REGULATORY INFORMATION

| 15.1 Safety, health a | nd environmental regulations/legislation specific for the substance or mixture |
|-----------------------|--|
| Approval code | MANUFACTURED ARTICLE |
| Group standard | Something for which its intended use is primarily to do with its physical shape, rather than its chemical composition. |
| Inventory listings | AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt. EUROPE:EINECS (European Inventory of Existing Chemical Substances) All components are listed on EINECS, or are exempt. NEW ZEALAND: NZIOC (New Zealand Inventory of Chemicals) All components are listed on the NZIoC inventory, or are exempt. UNITED STATES: TSCA (US Toxic Substances Control Act) All components are listed on the TSCA inventory, or are exempt. |



16. OTHER INFORMATION

| Additional information | EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation). |
|------------------------|---|
| | WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, ENGINEERING CONTROLS are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary. |
| | PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made. |
| | HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate. |
| Abbreviations | ACGIH American Conference of Governmental Industrial Hygienists CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds CCID Chemical Classification and Information Database (HSNO) CNS Central Nervous System EC No. EC No - European Community Number EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) EPA Environmental Protection Authority [New Zealand] GHS Globally Harmonized System HSNO Hazardous Substances and New Organisms IARC International Agency for Research on Cancer LC50 Lethal Dose, 50% / Median Lethal Dose mg/m³ Milligrams per Cubic Metre OEL Occupational Exposure Limit pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). ppm Parts Per Million STEL Short-Term Exposure Limit STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure) TLV Threshold Limit Value TWA Time Weighted Average |
| Report status | This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier. |
| | While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS. |

ChemAlert.

PRODUCT NAME 18V BATTERY 6.0AH HEAVY DUTY

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmtglobal.com

[End of SDS]

